



SIGN	DATE	DESCRIPTION	APPROVER

Technical Data:

Material:

- Contact(metal housing): Brass Machined.
- Terminal screw: Steel galvanized and achromatized.
- Solder Pin: Brass with Tin plated
- Insulator body(housing): Polyamide(Glass filled)(UL94V-0)

Electrical

- Voltage rating: 300VAC
- Current rating: 10 Amps/way max
- Contact resistance: 20m Ω (max)
- Insulation resistance: 5000M Ω /1000V
- Withstanding Voltage: 1500VAC(1min) Test time=60sec/1pcs
- Wire range: 12-22AWG

Mechanical:

- Torque: 4kgf.cm/M25
- Operating Temperature: -33°C to +120°C
- Soldering reliability: Test temperature= 250°C \pm 10°C 5 seconds max

POLE	3P	
A	NX5.0	15.0
B	(N-1) X5.0	10.0



杰科电子有限公司
JIE KE ELECTRONICS CO., LTD.

PART NAME: JK1271B-500 3P

TITLE:

PART NO.:

DWG NAME:

APPROVED BY

CHECKED BY

DESIGNED BY

DRAWN BY

CUSTOM NO.:

UNITS: mm

SCALE: 2:1

REVISION: B3

孙学峰

杨丽霞

杨丽霞

杨丽霞



Tolerance

X ±0.50

XX ±0.30

XXX ±0.10

X° ±1°